

S2624-4S Managed Gigabit Ethernet Switch



Product Description

28-Port Managed Gigabit Ethernet Switch, black iron shell design, built-in DC 12V Power supply, light and simple, with LED indicator on the panel, can dynamically display the connection and operation of equipment, provide simple fault detection methods, and facilitate maintenance and management; this series of switches provide advanced network management functions: redundant ring network, VLAN, cluster, QoS, speed control, port image, fault alarm and firmware online upgrade.

The adaptive port can automatically adapt to the 10m, 100m and 1000m networks, and can automatically adapt to the full duplex or half duplex mode; the MAC address self-learning function ensures error free data transmission; the store and forward mode prevents the damaged packets from flooding in the network; the flow control function can prevent the impact of a large amount of instantaneous data on the network; the port supports MDI/ Mdx auto flip function, non-blocking line speed transmission of all ports. It is mainly located in the core or convergence layer of user networks such as industrial parks, buildings, factories and mines, government agencies, community broadband, etc.; it can be widely used in Ethernet access scenarios such as small and medium-sized enterprises, Internet cafes, hotels, schools, etc.

Main Feature

Support 24* Gigabit Ethernet Ports+ 4* Gigabit SFP Ports+1* Console Port

Support IEEE802.3, IEEE802.3i, IEEE802.3u, IEEE802.3ab, IEEE802.3z, Storage and forwarding

Ethernet ports support 10/100/1000M adaptive

Adopt store-and-forward switching mechanism

Adopt store-and-forward switching mechanism

Fanless design, natural Cooling, 1U Rack Mount

Support 802.1x port authentication, support AAA authentication, support TACACS+ authentication

Support WEB, TELNET, CLI, SSH, SNMP, RMON management

Application Environment

Metro Optical Broadband Network: Data network operators such as telecommunications, cable TV, and network system integration, etc.

Broadband private network: Suitable for financial, government, oil, railway, electric power, public security, transportation, education and other industries

Multimedia transmission: Integrated transmission of images, voice and data, suitable for remote teaching, conference TV, videophone and other applications

Real-time monitoring: Simultaneous transmission of real-time control signals, images and data

CHARACTERISTICS

I/O Interface	
Power	AC INPUT (100-240V)
Ethernet	24* Gigabit Ethernet Ports 4* Gigabit SFP Ports 1* Console Port
Performance	
Bandwidth	56Gbps
Packet Forwarding Rate	41.66Mpps
Package Cache	4Mb
Memory	128M
Flash Memory	16M
MAC Address	8K
VLANs	4096
Jumbo Frame	9.6Kbytes
Transfer Mode	Storage & Forwarding
MTBF	100000 Hours
Standard	
Network Protocol	IEEE802.3 (Ethernet) IEEE802.3u (Rapid Ethernet) IEEE 802.3ab (Gigabit Ethernet)

	IEEE 802.3z (Gigabit Ethernet Optic Fiber) IEEE802.3x (Flow Control) IEEE 802.3az (Energy-efficient Ethernet) IEEE 802.3ad (Link aggregation) IEEE 802.1AB LLDP/LLDP-MED (Link Layer Discovery Protocol) IEEE 802.1D Spanning Tree Protocol STP IEEE 802.1w Rapid Spanning Tree Protocol RSTP IEEE 802.1s Multiple Spanning Tree Protocol MSTP IEEE 802.1Q (Virtual LAN) IEEE 802.1p (VLAN Label) IEEE 802.1X (User authentication)
Optical Medium	Multi-mode fiber: 50/125, 62.5/125, 100/140um Single mode fiber: 8/125, 8.7/125, 9/125, 10/125um
Network Medium	10Base-T: Cat 3, 4, 5 or above UTP(≤100m) 100Base-TX: Cat 5 or above UTP(≤100m) 1000Base-TX: Cat 5 or above UTP(≤100m)
Industry Standard	EMI: FCC Part 15 CISPR (EN55032) class A EMS: EN61000-4-2 (ESD), EN61000-4-4 (EFT), EN61000-4-5 (Surge)
Certification	
Safety Certification	CE, FCC, RoHS
Environment Standard	
Working Environment	Working Temperature: -10~50°C Storage Temperature: -40~70°C Working Humidity: 10%~90%, non-condensing Storage Humidity: 5%~90%, non-condensing
Function Indicator	
Indicator	PWR(Power Indicator); SYS(System Light); Link/Act(Link & Data)
PWR	On: Powered On

	Off: Powered Off
SYS	Off: System Off On: System On
Link/ACT	On: No Data Flashing: Data Transmit Off: Link Connection Blocked
Physical Specification	
Structure Size	Product Size: 440*204*44mm Package Size: 500*290*85mm Product N. W: 2.45kg Product G. W: 3.06kg
Packing Info	MEAS: 520*445*310MM Packing Qty: 5PCS Packing Weight: 16.3 KG
Power Voltage	Machine Input Voltage: AC 100-240V; Built-in power output: DC12V3A; Total Power: 36W
Package List	Switch: 1PCS; Power cable: 1PCS; Serial cable: 1PCS; Instruction manual: 1PCS; Certificate of quality: 1PCS; Warranty card: 1PCS; Mounting ear: 1 Pair

Software Function

Layer 2 Software Function	
Port Management	Enable/Disable Port
	Speed, Duplex, MTU Setting
	Flow-control
	Port Information Check
Port Mirroring	Supports both side-way port mirroring
Port Speed Limit	Support port rate limiting, the granularity of rate limiting is 32Kbps

Port Isolation	Support port isolation Settings
Storm Suppression	Supports unknown unicast, unknown multicast, and broadcast storm suppression
Link Aggregation	Support static manual aggregation Support LACP dynamic aggregation
VLAN	Access
	Trunk
	hybrid
	Support VLAN division based on port, protocol, and MAC address, VLAN tunnel
	Support GVRP dynamic VLAN registration
	Voice VLAN
MAC	Support static addition, deletion
	MAC address learning limit
	Support dynamic aging time setting
Spanning Tree	802.1D Spanning Tree Protocol (STP)
	802.1w Rapid Spanning Tree Protocol(RSTP)
	802.1s Multi Spanning Tree Protocol(MSTP)
Multicast	Support static addition, deletion, IGMP-snooping
	Support MLD-Snooping
	Support v1/2/3 dynamic multicast monitor
DDM	Support SFP/SFP+DDM
Layer 3 Function	
Routing Function	Static routing
IP	IPV4, IPV6 Interface
ARP	Support ARP
Extended Function	
ACL	Based on source MAC, destination MAC, protocol type, source IP, destination IP, L4 port
QOS	Based on 802.1p (COS) classification
	Based on DSCP classification
	Classification based on source IP, destination IP, and port number
	Support SP, WRR scheduling strategy

	Support flow rate limit CAR
LLDP	Support LLDP link discovery protocol
User Setting	Add/delete users
Log	User login, operation, status, events
Anti-attack	DOS Defense
	Support CPU protection and limits the rate of sending CPU packets
	ARP binding (IP, MAC, PORT binding)
Certification	Support 802.1x port authentication
	Support AAA certification
Network diagnosis	Support ping, telnet, trace
System Management	Device reset, configuration save/restore, upgrade management, time setting, etc
Management Function	
CLI	Support serial port command line management
SSH	Support SSHv1/2 remote management
TELNET	Support telnet remote management
WEB	Support Layer 2 settings, Layer 2 and Layer 3 monitor
SNMP	SNMP V1/V2/V3
	Support trap: ColdStart, WarmStart, LinkDown, LinkUp
RMON	Support RMON v1
Other Functions	Support DHCP Snooping, Option82, DHCP Server
Other Functions	Support dynamic ARP detection
	Support TACACS+ certification
	Support DNS Setting
	Support port security setting
	Support MVR protocol
	Support cable detection VCT function
	Support UDLD protocol